



420 N. Roosevelt Ave. • Chandler AZ 85226
1-800-528-8242 • (602) 276-0406 • FAX (480) 961-0513
www.crafco.com

PRODUCT DATA SHEET

HP ALL SEASON ASPHALT COLD PATCH

PART NO. 34977

MARCH 2011

READ BEFORE USING THIS PRODUCT

GENERAL Crafcro HP Asphalt Cold Patch is a black, cold applied, single component pavement patching material for repairing potholes, asphalt spalls, cracks and other pavement voids and distresses over 1 ½ inches wide. It can be used to repair roads, driveways and walkways. HP Asphalt Cold Patch is specially formulated to be used in most weather conditions and to adhere in cold and damp pavements. No mixing, heating or special application equipment is required. HP Asphalt Cold Patch develops its strength after compaction by tampers, vehicle tires or traffic, thus making the patching material suitable for use in “throw and go” repair situations. HP Asphalt cold patch is supplied in two grades. The L grade is an easier flowing material for applications when the weather is cooler. The M grade is for applications when the weather is warmer.

APPLICATION It is recommended that the repair area be swept clean of all debris and blown out before Application. Apply HP Asphalt Cold Patch to a height of ½ inch above the area surrounding the hole to be repaired. Do not apply less than 1 inch of material. Deep areas can be filled by adding material after compaction to build thickness, using 1-2 inch material lifts. Compact the material to a level surface with a tamper or vehicle tire. The repair area can be opened to traffic as soon as the compaction is complete. Initial surface tack can be reduced with a light sprinkle application of Portland Cement or calcium carbonate over the compacted surface.

PACKAGING Packaging consists of individual 50 pound plastic bags which are palletized into shipping units. Each pallet contains 60 bags. Palletized units are protected from the weather using a three mil thick plastic bag, a weather and moisture resistant cap sheet and a minimum of two layers of six month u.v. protected stretch wrap. Pallets are labeled with the product part number, lot number and net weight. Application Instructions are provided on the bag.

WARRANTY CRAFCO, Inc. warrants that CRAFCO products meet applicable specifications at time of shipment. Techniques used for the preparation of the areas to be repaired are beyond our control as are the use and application of the product; therefore, Crafcro shall not be responsible for improperly applied or misused product. Remedies against Crafcro, Inc., as agreed to by Crafcro, are limited to replacing nonconforming product or refund (full or partial) of purchase price from Crafcro, Inc. All claims for breach of this warranty must be made within three (3) months of the dated of use or twelve (12) months from the date of delivery by Crafcro, Inc. whichever is earlier. There shall be no other warranties expressed or implied. For optimum performance, follow Crafcro recommendations for product installation.